

## Handled Ultrasonic Flowmeter



### ► Feature

- ✓ **High Accuracy**  
Accuracy better than 1%.
- ✓ **Wide Measurement Range**  
Measurement range from DN15~DN6000mm
- ✓ **Rechargeable Power Supply**  
Built-in high-capacity NiMH rechargeable batteries will last more than 10 hours(Fully charged).
- ✓ **Non invasion measurement**  
Can achieve measurement with clamp on sensors
- ✓ **Data Storage**  
32K BIT built-in data storage,can store two thousand rows of data
- ✓ **LCD display**  
LCD display can display the instant flow,total flow,flow velocity and working condition

# Handled Ultrasonic Flowmeter


## ➤ Product Introduction

The AFT handled ultrasonic flowmeter is designed to work with clamp-on transducers to enable the flow of a liquid within a closed pipe to be measured accurately without needing to insert any mechanical parts through the pipe wall or protrude into the flow system.

Using ultrasonic transit time techniques, the is controlled by a micro-processor system which contains a wide range of data that enables it to be used with pipes with an outside diameter ranging from 15mm up to 6000mm (depending on model) and constructed of almost any material. The instrument will also operate over a wide range of fluid temperatures.

### Clamp on transducer

- ◆ Easy to install and no need to cut off the flow, no pressure loss
- ◆ Different transducer from DN15~DN6000
- ◆ Different transducer for temperature -30~160°C




- ◆ Reduces installation time, improve installation accuracy
- ◆ Easy installation, no need cut the flow, no pressure loss
- ◆ Easy to install and no need to cut off the flow, no pressure loss
- ◆ Different transducer from DN15~DN700
- ◆ Different transducer for temperature -30~160°C



# Handled Ultrasonic Flowmeter

## ► The main components feature



## ► Optional transducer

Type	Picture	Size	Model	Measuring range	Temperature	Dimension
Standard Clamp on Type		Small	S2	DN15~DN100	-30~90℃	45×25×32mm
		Medium	M2	DN50~DN700	-30~90℃	64×39×44mm
		Large	L2	DN300~DN6000	-30~90℃	97×54×53mm
High Temperature Clamp on Type		Small	S2H	DN15~DN100	-30~160℃	45×25×32mm
		Medium	M2H	DN50~DN700	-30~160℃	64×39×44mm
		Large	L2H	DN300~DN6000	-30~160℃	97×54×53mm
Standard Bracket Type		Small	S2B	DN15~DN100	-30~90℃	318×59×85mm
		Medium	M2B	DN100~DN300	-30~90℃	568×59×85mm
		Large	L2B	DN300~DN700	-30~90℃	188×59×49mm
High Temperature Bracket Type		Small	S2BH	DN15~DN100	-30~160℃	318×59×110mm
		Medium	M2BH	DN100~DN300	-30~160℃	568×59×110mm
		Large	L2BH	DN300~DN700	-30~160℃	188×59×49mm

# Handled Ultrasonic Flowmeter

## Basic Technical Parameter

Type		Performance parameter
<b>Transmitter</b>	Principle	Ultrasonic transit-time principle, Four-byte IEEE754 floating arithmetic
	Accuracy	Flow: Better than $\pm 1\%$
	Display	LCD display with Chinese, English, Italian language
	Output	One OCT pulse output(pulses width 6-1000ms, Default 200ms)
	Data interface	Isolation of 232 communication interface, can upgrade flowmeter through PC
<b>Pipeline Conditions</b>	Pipe Material	Steel, Stainless steel, Cast iron, copper, PVC, aluminium, FRP etc.(liner allowed)
	Diameter	15~6000mm
	Installation	Upstream 10D,downstream 5D,30D away from the pump outlet(D for diameter)
<b>Medium</b>	Fluid	Water,sea water,acid liquid,beer,alcohol,oil and any other liquid that can spread sonic
	Temperature	Temperature: -30~160°C
	Turbidity	10000ppm and with little bubbles
	Velocity	0~ $\pm 10$ m/s
<b>Operating Environment</b>	Temperature	Transmitter: -20~60°C; Transducer: -30~160°C
	Humidity	Transmitter: 85%RH; transmitter protection grade: IP67
<b>Power</b>	Three internal 1.2V, 2000mAH rechargeable Ni-MH battery. Can work 12 hours fully charged. Can achieve continuous measurement with AC100-240V power adapter	
<b>Consumption</b>	1.5W	
<b>Case Material</b>	Flame retardant ABS	
<b>Weight</b>	Transmitter: 514g	